

-19-

## CLAIMS

1. A DC-DC converter of a charge pump type,  
comprising:

5           a constant voltage circuit part configured to  
convert an input voltage into a first voltage and output the  
first voltage from a first output terminal;

          a charge pump circuit part configured to convert the  
first voltage input from the constant voltage circuit part  
10 into a second voltage and output the second voltage from a  
second output terminal;

          a current detection circuit part configured to  
convert an output current of the constant voltage circuit part  
into a third voltage and output the third voltage;

15           a first output voltage detection circuit part  
configured to detect the first voltage at the first output  
terminal and generate and output a first detection voltage  
proportional to the detected first voltage;

          a first overcurrent protection circuit part  
20 configured to compare the output third voltage and the output  
first detection voltage and reduce the output first voltage  
and the output current of the constant voltage circuit part  
when the output third voltage is higher than the output first  
detection voltage;

25           a second output voltage detection circuit part

-20-

configured to detect the output second voltage of the charge pump circuit part and generate and output a second detection voltage proportional to the detected second voltage; and

a second overcurrent protection circuit part

5 configured to compare the output third voltage and the output second detection voltage and reduce the output first voltage and the output current of the constant voltage circuit part when the output third voltage is higher than the output second detection voltage.

10

2. The DC-DC converter as claimed in claim 1, wherein the first output voltage detection part generates and outputs the first detection voltage so that the first detection voltage is higher than the second detection voltage  
15 when the output first voltage of the constant voltage circuit part is higher than the output second voltage of the charge pump circuit part.

3. The DC-DC converter as claimed in claim 1, wherein the first overcurrent protection circuit part operates  
20 when the output first voltage of the constant voltage circuit part is lower than the output second voltage of the charge pump circuit part.

25

4. The DC-DC converter as claimed in claim 1,

-21-

wherein the second overcurrent protection circuit operates when the output second voltage of the charge pump circuit part is lower than the output first voltage of the constant voltage circuit part.

5

5. A DC-DC converter of a charge pump type, comprising:

a constant voltage circuit part configured to convert an input voltage into a first voltage and output the first voltage from a first output terminal;

a charge pump circuit part configured to convert the first voltage input from the constant voltage circuit part into a second voltage and output the second voltage from a second output terminal;

15 a current detection circuit part configured to convert an output current of the constant voltage circuit part into a third voltage and output the third voltage;

a first output voltage detection circuit part configured to detect the first voltage at the first output terminal and generate and output a first detection voltage proportional to the detected first voltage;

20 a first overcurrent protection circuit part configured to compare the output third voltage and the output first detection voltage and reduce the output first voltage and the output current of the constant voltage circuit part

25

-22-

when the output third voltage is higher than the output first detection voltage;

second output voltage detection means for detecting the output second voltage of the charge pump circuit part and  
5 generating and outputting a second detection voltage proportional to the detected second voltage; and

second overcurrent protection circuit means for comparing the output third voltage and the output second detection voltage and reducing the output first voltage and  
10 the output current of the constant voltage circuit part when the output third voltage is higher than the output second detection voltage.